EMA Series



Bottle and Liquid Scanner

NSNs: 6665-151805235 / 6665-151805236





EXAMPLES OF BOTTLES
THAT CAN BE SCREENED WITH EMA



OPTIONAL EXTERNAL PROBE (TYPE A)
FOR SAMPLED LIQUID ANALYSIS

- Accurate and Quick Inspection
 of bottles against dangerous
 substances, such as combustible,
 flammable and explosive liquids
- Clear "OK/Attention" inspection result Type B BLS with embedded type A
- Automatic Analysis of sealed containers in ~ 5 seconds
- Inspection of bottles or containers:
 - ✓ independently of their shape
 - ✓ made of different materials
 - \checkmark in a wide range of capacity

- Compliant with current BLS detection and discrimination requirements
- Verified and Qualified by Governmental Security Authorities
- Type B BLS with embedded type A analyzer (optional)
- Analysis of the entire volume
 without the need to open the bottle
- Verification of sealed metal cans
- Compact size and ergonomic design
- Construction in stainless steel for maximum life and hygiene



www.ceia.net

EMA Bottle and Liquid Scanner

NSNs: 6665-151805235 / 6665-151805236

The EMA is a compact device designed for the analysis of bottles and their contents with the goal of detecting the possible presence of combustible, flammable and explosive liquids. When the operator places the bottle in the inspection cavity, its presence is automatically detected and the analysis process starts.

The entire volume of the bottle is analyzed in order to verify its conformity with benign liquids. After a few seconds, the unit provides an OK or Alarm message without requiring any data interpretation by the operator. Calibration is carried out automatically by the unit.

The electromagnetic fields generated in the inspection cavity are weak in intensity and non-ionizing, therefore **completely safe for the liquids and for the operator**.

If the results of the measurements do not conform to the characteristics of innocuous liquids (e.g. soft drinks, water, wine, liquor), **EMA** provides an acoustic and red light alarm and a message requiring further inspection of the content.

If the results of the measurements correspond to the characteristics of innocuous liquids, EMA returns the "OK" message and a green light.

SPECIFICATIONS _

WORKING DETECTION PRINCIPLE

- Wideband RF Complex Impedance measurement
- Multiple sensing technology

INSPECTION CHARACTERISTICS

- Commercial Bottles of any shape and in a wide range of dimensions can be analyzed with capacity ranging from 100 ml to 2000 ml
- Initial Start-up time: 15 sec. max
- Analysis type: automatic
- Analysis time: 5 sec. typical

DETECTABLE SUBSTANCES

• Combustible, flammable and explosive liquids

ALARM/NO ALARM AND DIAGNOSTIC SIGNALLING

Visual, with display indication:

- green "OK"
- yellow "Diagnostic"
- red "Alarm"

OPERATOR INTERFACE

- Easy to read high-contrast graphic display
- High durability stainless steel function keys
- Programmability of all the parameters protected by passwords

FUNCTION AND CALIBRATION CONTROL

- Automatic calibration, continuously running
- Manual verification of calibration, performed by the operator through Pass/No-Pass reference test pieces (according to the operational procedures)

COMMUNICATION CAPABILITY

- RS-232 serial interface
- Ethernet network interface

REMOTE CONTROL AND ETHERNET NETWORKING FUNCTIONS AVAILABLE THROUGH THE CEIA NetID MANAGEMENT SOFTWARE

- Programming
- Statistical Data Collection
- Maintenance
- Firmware upgrade

OVERALL DIMENSIONS

- 470 mm x 317 mm x 330 mm w/o external probe
- 545 mm x 317 mm x 330 mm with external probe

WEIGHT

- 17 kg w/o external probe
- 17.5 kg with external probe

DEGREE OF PROTECTION: IP 20 (IEC 60529)

MAIN MECHANICAL FEATURES

- Constructed entirely in AISI304 Stainless Steel
- Anti-fingerprint surface treatment
- Rugged and Durable
- Compact and Aesthetically pleasing

MAIN ELECTRONICS FEATURES

- High integration SMT
- 32-bit flash-based microcontrollers
- 32-bit DSP
- Low power and high reliability
- Very low power inspection field, confined in the analysis compartment, completely safe for both the operator and the liquid
- No ionizing radiation
- No radioactive sources

INSTALLATION AND MAINTENANCE

- Automatic adjustment to environmental conditions
- No initial or periodic calibrations required
- Firmware upgradeable via RS232 or Ethernet interface
- No periodical maintenance or consumables required
- Built-in self-diagnosis system

CERTIFICATION AND CONFORMITY

 Conforms to the currently applicable International Standards for Electrical Safety and FMC

POWER SUPPLY: $115/230V \sim \pm 15\%$, $50/60 \text{ Hz} \pm 10\%$, 15W

ENVIRONMENTAL CONDITIONS

- Operating temperature: +10°C to +40°C
- Storage temperature: -10°C to +60°C
- Operating Relative humidity:
 Ota 95% (without condensation)
- 0 to 95% (without condensation)
- Storage Relative humidity: 0-98%, without condensation
- NATO STOCK NUMBER: 6665-151805235

• 6665-151805236

EXTERNAL PROBE (OPTIONAL)

EMA is designed for the analysis of beverages in their original container. In case of open containers such as cups and thermos flasks, it is possible to carry out the analysis by means of an optional external probe, using small disposable plastic sample cups. The external probe is installed on the right side of the device. Analysis time: 2 sec.

OPERATIONAL SEQUENCE



THE OPERATOR INSERTS THE CONTAINER TO BE CHECKED AND LEAVES IT IN THE INSPECTION CAVITY



THE ANALYSIS IS ACTIVATED AUTOMATICALLY.
THE DISPLAY SHOWS THE ANALYSIS PROGRESS



IF THE CONTAINER CONTENT IS IDENTIFIED AS NOT DANGEROUS, THE "OK" MESSAGE AND A GREEN LIGHT ARE DISPLAYED. A SHORT ACOUSTICAL "BEEP" IS GENERATED



IF THE CONTAINER CONTENT IS IDENTIFIED AS POTENTIALLY DANGEROUS, THE MESSAGE "ATTENTION - NOT ALLOWED PRODUCT" AND A RED LIGHT ARE DISPLAYED. AN ACOUSTICAL "BEEP" IS GENERATED



Zona Industriale 54/G, 52041 Viciomaggio - Arezzo (ITALY)
Tel.: +39 0575 4181 Fax: +39 0575 418298 E-mail: infosecurity@ceia-spa.com